



## HARMANLUXURYAUDIO - JBL PREMIUM LOUDSPEAKERS

RETAIL PRICE LIST October 2021

## Table of Contents

Everest and K2 Series Floor Standing Loudspeakers .....	3
“S” Series Floor Standing Loudspeakers.....	4
Studio Monitors .....	5
Classic Series .....	7
HDI Series .....	9
SA750 Integrated Amplifier .....	11
Terms and Conditions .....	13

# JBL PREMIUM LOUDSPEAKERS

## Everest & K2 Series Floorstanding Loudspeakers



Model Name	Description	Material Number	MSRP
Project Everest DD67000	<p>3-Way Floor Standing Loudspeaker</p> <ul style="list-style-type: none"> <li>• Two 15" (38.1 cm) woofers</li> <li>• 4" (10.2 cm) pure-beryllium diaphragm for crystal-clear highs</li> <li>• 1" (2.5 cm), pure-beryllium diaphragm for extreme highs</li> <li>• Self-charged Crossover network; Provides more transparent and detailed voicing with lower distortion (Class A Operation)</li> <li>• Frequency Response 29 Hz – 60 kHz (half space); 45 Hz – 60 kHz (anechoic)</li> <li>• Recommended Amplifier Power: 500 watts</li> <li>• Sensitivity (2.83V @ 1m) 96dB Nominal Impedance 8 ohms; 5.0 ohms @ 80 Hz; 3.0 ohms @40 kHz</li> <li>• Dimensions (H x W x D): 43.7" x 38" x 18.5" (110.9 cm x 96.5 cm x 47 cm)</li> <li>• Weight: 313 lb (142.1 kg)</li> <li>• Packaged dimensions (H x W x D): 28" x 53.1" x 49.8" (712 x 1350 x 1265 mm)</li> <li>• Packaged weight: 573 lb (260 kg)</li> <li>• Rosewood (RW) Finish with textured carbon fiber baffle.</li> <li>• <b>120 day lead time from issue of customer PO</b></li> </ul>	DD67000RW (RoseWood)	<b>94.000 € /pair</b>
Project K2 S9900	<p>3-Way Floor Standing Loudspeaker</p> <ul style="list-style-type: none"> <li>• 15" (38.1 cm) woofer</li> <li>• 4" (10.2 cm) Magnesium high-frequency compression driver with Bi-Radial® horn</li> <li>• 1" (2.5 cm) Beryllium ultrahigh-frequency compression driver with Bi-Radial® horn</li> <li>• Frequency Response 48 Hz – 50 kHz</li> <li>• Low Frequency Extension 33 Hz</li> <li>• Recommended Amplifier Power 500 Watts</li> <li>• Sensitivity (2.83V @ 1m) 93dB</li> <li>• Nominal Impedance 8 ohms, 7 ohms minimum at 100 Hz, 4 ohms minimum at 40 kHz</li> <li>• Dimensions (H x W x D): 47.3" x 22" x 13.8" (120.1 cm x 55.9 cm x 35 cm)</li> <li>• Weight: 182 lb (82.7 kg)</li> <li>• Packaged dimensions (H x W x D): 20.1" x 51.6" x 27.2" (510 x 1310 x 690 mm)</li> <li>• Packaged weight: 202 lb (91.5 kg)</li> <li>• Wood grain or black zebra wood (ZW) finish</li> <li>• <b>120 day lead time from issue of customer PO</b></li> </ul>	NK2S9900 (Wood grain)  NK2S9900ZW (Zebra Wood)	<b>54.500 € / pair</b>



# JBL PREMIUM LOUDSPEAKERS

## S Series Floorstanding Loudspeakers



Model Name	Description	Material Number	MSRP
S4700	<p>3-Way Floor Standing Loudspeaker</p> <ul style="list-style-type: none"> <li>• 380 mm (15") pure pulp cone with</li> <li>• 380 mm (15") pure pulp cone with treated cloth edge and Differential Drive® (U.S. patent no. 5,748,760 and other patents pending) neodymium motor assembly</li> <li>• 1.8" (4.6 cm) Aqua-Plas-coated titanium diaphragm high frequency compression driver with Bi-Radial® horn</li> <li>• 0.75" (1.9 cm) Titanium diaphragm ultrahigh frequency compression driver with Bi-Radial® horn</li> <li>• Maximum recommended amplifier power: 300 watts RMS</li> <li>• Frequency response: 38 Hz – 40 kHz (–6dB)</li> <li>• Nominal impedance: 6 ohms</li> <li>• Sensitivity: 94dB (2.83V/1m)</li> <li>• Dimensions (H x W x D): 42.1" x 19.7" x 14.6" (106.8 cm x 50.0 cm x 37.1 cm)</li> <li>• Weight: 120 lb (54.5 kg)</li> <li>• Packaged dimensions (H x W x D): 20.1" x 46.3" x 24.6" (510 x 1175 x 625 mm)</li> <li>• Packaged weight: 139 lb (63.2 kg)</li> <li>• Cherry wood finish</li> </ul> <p><b>Special order</b></p> <ul style="list-style-type: none"> <li>• 120 day lead time from issue of customer PO</li> <li>• Custom finish Black Gloss</li> <li>• Limited Availability</li> </ul>	S4700	<b>18.000 € / pair</b>
		S4700BG	<b>19.900 € / pair</b>
S3900	<p>3-Way Floor Standing Loudspeaker</p> <ul style="list-style-type: none"> <li>• Two 10" (25 cm) pure-pulp cones with ferrite motor assemblies</li> <li>• 1.8" (4.6 cm) compression driver with an Aquaplas-treated pure-titanium diaphragm and neodymium motor assembly on a SonoGlass® Bi-Radial horn</li> <li>• .75" (1.9 cm) compression driver with a pure titanium diaphragm and neodymium motor assembly on a SonoGlass Bi-Radial horn</li> <li>• Maximum recommended amplifier power: 250 watts</li> <li>• Frequency response: 33 Hz – 40 kHz (–6dB)</li> <li>• Nominal impedance: 6 ohms</li> <li>• Sensitivity: 92dB (2.83V/1m)</li> <li>• Dimensions (H x W x D): 39.4" x 14.6" x 14.5" (100.1 cm x 37 cm x 36.8 cm)</li> <li>• Weight: 86 lb (39 kg)</li> <li>• Packaged dimensions (H x W x D): 19.3" x 43.3" x 20.1" (490 x 1100 x 510 mm)</li> <li>• Packaged weight: 105 lb (47.5 kg)</li> <li>• Cherry wood finish</li> </ul> <p><b>Special order</b></p> <ul style="list-style-type: none"> <li>• 120 day lead time from issue of customer PO</li> <li>• Custom finish Black Gloss</li> <li>• Limited Availability</li> </ul>	S3900	<b>12.200 € / pair</b>
		S3900BG	<b>14.100 € / pair</b>

# JBL PREMIUM LOUDSPEAKERS

## Studio Monitors



Model Name	Description	Material Number	MSRP
4367	<p>2-way Floorstanding Loudspeaker</p> <ul style="list-style-type: none"> <li>• Low-Frequency Transducer: 15" (380 mm) 2216Nd-1 Differential Drive® woofer</li> <li>• Mid/High Frequency Transducer: 3" (75 mm) D2430K dual compression</li> <li>• Maximum Recommended Amplifier Power: 300 watts RMS</li> <li>• Frequency Response (-6dB): 30 Hz – 40 kHz</li> <li>• Sensitivity (2.83V@1M): 94dB</li> <li>• Nominal Impedance: 6 Ohm</li> <li>• Crossover Frequencies: 700 Hz</li> <li>• Enclosure Type: Bass-reflex via Dual Front-firing Ports</li> <li>• Inputs: Dual Gold-plated Five-way Binding Posts</li> <li>• Dimensions (H X W X D): 37-1/16" x 22-1/16" x 16-3/4" (941 x 560 x 425 mm)</li> <li>• Weight: 135 lb (61.2 kg)</li> <li>• Packaged dimensions (H x W x D): 24.6" x 42.5" x 29.1" (625 x 1080 x 740 mm)</li> <li>• Packaged weight: 156 lb (70.8 kg)</li> </ul>	4367WX 4367BX	<b>8.930 € / piece</b>
4349	<p>2-way 12" Studio Monitor Loudspeaker</p> <ul style="list-style-type: none"> <li>• Impedance: 8 Ohms</li> <li>• Maximum Recommended Amplifier Power: 200 Watts RMS</li> <li>• Sensitivity (2.83V/1m): 91dB</li> <li>• Frequency Response: 32 Hz–25 kHz (-6dB)</li> <li>• Crossover Frequency: 1.7 kHz</li> <li>• Input Type: Dual gold-plated five-way binding posts</li> <li>• Finishes: Black Woodgrain Veneer</li> <li>• Dimensions with Grille (H x W x D): 29" x 17.5" x 13.5" (737 x 445 x 343 mm)</li> <li>• Weight: 80.6 lbs (36.6 kg)</li> </ul>	JBL4349BLK	<b>4.600 € / piece</b>
4312G	<p>12", 3-way Studio Monitor</p> <ul style="list-style-type: none"> <li>• Low-frequency transducer: 300 mm pure-pulp cone woofer (JW300SW-8)</li> <li>• Mid-frequency transducer: 125 mm pure pulp cone (JM125PC-8)</li> <li>• High-frequency transducer: 25 mm Magnesium-Aluminum alloy dome (054ALMg-1)</li> <li>• Recommended amplifier power: 10-200 watts RMS</li> <li>• Frequency response: 44 Hz – 40 kHz (-6dB)</li> <li>• Nominal impedance: 6 ohms</li> <li>• Sensitivity: 90dB (2.83V/1m)</li> <li>• Crossover frequencies: 640 Hz, 5 kHz</li> <li>• Controls: Attenuators for MF and HF drivers</li> <li>• Enclosure type: Bass-reflex via front-firing port</li> <li>• Connector type: Dual gold-plated five-way binding posts</li> <li>• Finish: Black woodgrain</li> <li>• Grille color: Black</li> <li>• Dimensions (H x W x D): 597 mm x 362 mm x 305 mm (23-1/2" x 14-1/4" x 12")</li> <li>• Weight: 23.8 kg (52.4 lb) / Packaged weight: 130 lb (58.8 kg)</li> </ul>	JBL4312GBLKEU <i>Packed and sold in pairs</i>	<b>3.100 € / pair</b>
JS-120 Stands	<p>Designed for JBL 12" monitors, including L100 Classic, 4349, and 4312G.</p> <p><i>Packed and sold in pairs.</i></p>	JBLJS120BLK	<b>390 € / pair</b>

# JBL PREMIUM LOUDSPEAKERS



## Studio Monitors



Model Name	Description	Material Number	MSRP
4309	<p>Type: 2-way bookshelf loudspeaker</p> <ul style="list-style-type: none"> <li>• Low Frequency Driver: 6.5" (165mm)</li> <li>• Pure Pulp cone woofer</li> <li>• High Frequency Driver: 2410H-2 1-inch (25mm) annular ring, Teonex® diaphragm compression driver with advanced HDI™ geometry horn</li> <li>• Recommended Amplifier Power: 25 – 150 WRMS</li> <li>• Impedance: 4 Ohm</li> <li>• Loudspeaker Sensitivity: 87dB/2.83V/1m</li> <li>• Frequency Response: 42Hz – 30kHz (-6dB)</li> <li>• Coverage Angle, -6dB: 100 Degrees Hor. x 80 Degrees Ver., from 2kHz to 17kHz</li> <li>• Crossover Frequency: 1.6kHz</li> <li>• Enclosure Type: V-braced front-ported bookshelf</li> <li>• Grille Feature: Monitor style to match horn mating features, supplied in dark blue (with walnut cabinet) and black (with black cabinet)</li> <li>• Dimensions with grille: 16.5" H x 10.25" W x 9" D (419mm H x 260mm W x 227mm D)</li> <li>• Controls: UHF tone control</li> <li>• Input Type: Dual sets of gold-plated binding posts with shorting straps</li> <li>• Product Weight (Each): 24.2 lbs (10.98kg)</li> <li>• Shipping Weight: 56.2 lbs (25.5kg)</li> <li>• Shipping Units of Measure: Pair</li> <li>• Warranty: 5 Years</li> <li>• Recommended stand height: 24" (609mm)</li> </ul> <p>JBL 4309 6.5-inch (165mm) 2-way Studio Monitor Loudspeaker</p>	JBL4309BLK	<b>2.440 € / pair</b>

# JBL PREMIUM LOUDSPEAKERS

## Classic Series



Model Name	Description	Material Number	MSRP
L100 Classic	<p>3-way Bookshelf Loudspeaker</p> <ul style="list-style-type: none"> <li>• Low-Frequency Transducer: 12" (300 mm) pure pulp cone woofer (JW300PW-8)</li> <li>• Mid-Frequency Transducer: 5.25" (125 mm) polymer-coated pure pulp cone (105H-1)</li> <li>• High-Frequency Transducer: 1" (25 mm) titanium dome with soft surround (JT025TI-4)</li> <li>• Maximum Recommended Amplifier Power: 200 watts RMS</li> <li>• Frequency Response (-6dB): 40 Hz – 40 kHz</li> <li>• Sensitivity (2.83V@1M): 90dB</li> <li>• Nominal Impedance: 4 Ohms</li> <li>• Crossover Frequencies: 450 Hz, 3.5 kHz</li> <li>• Controls: Attenuators for MF and HF drivers</li> <li>• Inputs: Five-way gold-plated binding posts</li> <li>• Dimensions (H X W X D): 25.06" x 15.34" x 14.625" (941 mm x 560 mm x 425 mm)</li> <li>• Weight: 58.5 lb (26.7 kg)</li> <li>• Finishes: Genuine walnut veneer enclosure with quadrex foam grille</li> </ul> <p><b>Note: For optimum performance, use with JS-120 Floor Stands</b></p>	<p>JBLL100CLASSICBLK</p> <p>JBLL100CLASSICORG</p> <p>JBLL100CLASSICBLU</p>	<b>4.700 € / pair</b>
JS-120 Stands	<p>Designed for JBL 12" monitors, including L100 Classic, 4349, and 4312G.</p> <p><b>Packed and sold in pairs.</b></p>	JBLJS120BLK	<b>390 € / pair</b>
L100 Classic Grilles	<p>Extra grilles can be purchased separately as an accessory.</p>	<p>JBLL100GLBLK</p> <p>JBLL100GLORG</p> <p>JBLL100GLBLU</p>	<b>450 € / pair</b>
L82 Classic	<p>2-way bookshelf loudspeaker</p> <ul style="list-style-type: none"> <li>• Low Frequency Driver Size and Material: 8" (200 mm) Pure Pulp cone woofer (JW200PW-6)</li> <li>• High Frequency Driver Size and Material: 1" (25 mm) Titanium dome tweeter (JT025TI1-4)</li> <li>• Recommended Amplifier Power: 25 - 150 WRMS</li> <li>• Impedance: 8 Ohm</li> <li>• Loudspeaker Sensitivity: 88dB/2.83V/1m</li> <li>• Frequency Response: 44 Hz – 40 kHz (-6dB)</li> <li>• Crossover Frequency: 1.7 kHz</li> <li>• Enclosure Type: Front-ported bookshelf</li> <li>• Enclosure Finish: Genuine walnut veneer</li> <li>• Grille Colors: Orange, Black, Blue</li> <li>• Controls: HF level control</li> <li>• Input Type: Dual gold-plated binding posts</li> <li>• Dimensions with grille: 18.61" H x 11.06" W x 11.65" D (472.8 mm x 281 mm x 296 mm)</li> <li>• Weight: 27.9 lb (12.7 kg)</li> </ul> <p><b>Packed and sold in pairs.</b></p>	<p>JBLL82CLASSICORG</p> <p>JBLL82CLASSICBLK</p> <p>JBLL82CLASSICBLU</p>	<b>2.465 € / pair</b>
JS80 Stands	<p>Accessory floorstands for JBL L82 Classic loudspeakers</p> <p><b>Packed and sold in pairs.</b></p>	JBLJS80STANDBLK	<b>215 € / pair</b>
LS82 Classic Grilles	<p>Extra grilles can be purchased separately as an accessory.</p> <p><b>Packed and sold in pairs.</b></p>	<p>JBLL82GLBLK</p> <p>JBLL82GLORG</p> <p>JBLL82GLBLU</p>	<b>225 € / pair</b>

# JBL PREMIUM LOUDSPEAKERS

## Classic Series



Model Name	Description	Material Number	MSRP
L52 Classic	<p>2-way bookshelf loudspeaker</p> <ul style="list-style-type: none"> <li>• Low Frequency Driver: 5.25" (133mm) Pure Pulp cone woofer (JW135PW-4)</li> <li>• High Frequency Driver: 0.75" (20mm) Titanium dome tweeter (JT020T1-4) with waveguide</li> <li>• Recommended Amplifier Power: 10 – 75 WRMS</li> <li>• Impedance: 4 Ohm</li> <li>• Loudspeaker Sensitivity: 85dB/2.83V/1m</li> <li>• Frequency Response: 47Hz – 24kHz (-6dB)</li> <li>• Crossover Frequency: 2.8kHz</li> <li>• Enclosure: Front-ported bookshelf in satin walnut furniture-grade wood veneer</li> <li>• Grille: Foam Quadrex grille available in three colors: black, burnt orange and dark blue</li> <li>• Dimensions with grille: 13" H x 7.74" W x 8.51" D (330.2mm x 196.6mm x 216.2mm)</li> <li>• Controls: HF level control</li> <li>• Input Type: Gold-plated binding posts</li> <li>• Product Weight (Each): 11 lbs. (5.0kg)</li> <li>• Shipping Weight: 30.4 lbs. (13.8kg)</li> </ul> <p>• Packed and sold in pairs.</p>	<p>JBLL52CLASSICORG JBLL52CLASSICBLK JBLL52CLASSICBLU</p>	<p><b>1.220 € / pair</b></p>
L100 Classic 75 <sup>th</sup> Special Edition	<p>3-way Bookshelf Loudspeaker</p> <ul style="list-style-type: none"> <li>• Low-Frequency Transducer: 12" (300 mm) pure pulp cone woofer (JW300PW-8)</li> <li>• Mid-Frequency Transducer: 5.25" (125 mm) polymer-coated pure pulp cone (105H-1)</li> <li>• High-Frequency Transducer: 1" (25 mm) titanium dome with soft surround (JT025T1-4)</li> <li>• Maximum Recommended Amplifier Power: 200 watts RMS</li> <li>• Frequency Response (-6dB): 40 Hz – 40 kHz</li> <li>• Sensitivity (2.83V @1M): 90dB</li> <li>• Nominal Impedance: 4 Ohms</li> <li>• Crossover Frequencies: 450 Hz, 3.5 kHz</li> <li>• Controls: Attenuators for MF and HF drivers</li> <li>• Inputs: Five-way gold-plated binding posts</li> <li>• Dual-input/bi-amp network</li> <li>• Updated woofer and tweeter</li> <li>• Certificate of authenticity of the limited edition pair</li> <li>• Dimensions (H x W x D): 25.06" x 15.34" x 14.625" (941 mm x 560 mm x 425 mm)</li> <li>• Weight: 58.5 lb (26.7 kg)</li> <li>• Finishes: Teak veneer enclosure with quadrex foam grille</li> <li>• Delivered in a custom designed crate and includes JS-120 stands</li> </ul>	<p>JBLL100-75BLK</p>	<p><b>6.200 € / pair</b></p>



# JBL PREMIUM LOUDSPEAKERS

## HDI Series



Model Name	Description	Material Number	MSRP
HDI-3800	<p>2.5-Way Floorstanding Loudspeaker</p> <ul style="list-style-type: none"> <li>• 1" Teonex Compression Driver Tweeter</li> <li>• Triple 8" black aluminum cone, cast-frame woofers</li> <li>• High-Definition Imaging (HDI™) waveguide</li> <li>• Dual sets of gold-plated binding posts</li> <li>• Crossover frequencies: 800 Hz, 1800 Hz</li> <li>• Sensitivity (2.83 @ 1M): 92dB</li> <li>• Nominal impedance: 4Ω</li> <li>• Recommended amplifier power: 25-300 W</li> <li>• Frequency response: 37 Hz – 30 kHz</li> <li>• Three finishes available: Black Lacquer, Grey Oak and Walnut</li> <li>• Dimensions (H x W x D): 45.33" x 11.81" x 16.45"</li> <li>• Weight: 83.78 lbs</li> </ul>	<p>JBLHDI3800BLQ</p> <p>JBLHDI3800GRO</p> <p>JBLHDI3800WAL</p>	<b>5.170 € / pair</b>
HDI-3600	<p>2.5-Way Floorstanding Loudspeaker</p> <ul style="list-style-type: none"> <li>• 1" Teonex Compression Driver Tweeter</li> <li>• Triple 6.5" black aluminum cone, cast-frame woofers</li> <li>• High-Definition Imaging (HDI™) waveguide</li> <li>• Dual sets of gold-plated binding posts</li> <li>• Crossover frequencies: 900 Hz, 2000 Hz</li> <li>• Sensitivity (2.83V @ 1M): 90dB</li> <li>• Nominal impedance: 4Ω</li> <li>• Recommended amplifier power: 25-300 W</li> <li>• Frequency response: 38 Hz – 30 kHz</li> <li>• Three finishes available: Black Lacquer, Grey Oak and Walnut</li> <li>• Dimensions (H x W x D): 38.84" x 10.04" x 13.46"</li> <li>• Weight: 61.8 lbs</li> </ul>	<p>JBLHDI3600BLQ</p> <p>JBLHDI3600GRO</p> <p>JBLHDI3600WAL</p>	<b>3.750 € / pair</b>
HDI-4500	<p>2.5-Way Center Channel Loudspeaker</p> <ul style="list-style-type: none"> <li>• 1" Teonex Compression Driver Tweeter</li> <li>• Quadruple 5.25" black aluminum cone, cast-frame woofers</li> <li>• High-Definition Imaging (HDI™) waveguide</li> <li>• Dual sets of gold-plated binding posts</li> <li>• Crossover frequencies: 600 Hz, 2200 Hz</li> <li>• Sensitivity (2.83V @ 1M): 90dB</li> <li>• Nominal impedance: 4Ω</li> <li>• Recommended amplifier power: 20-250 W</li> <li>• Frequency response: 50 Hz – 30 kHz</li> <li>• Three finishes available: Black Lacquer, Grey Oak and Walnut</li> <li>• Dimensions (H x W x D): 7.48" x 33.13" x 12.3"</li> <li>• Weight: 44.33 lbs</li> </ul>	<p>JBLHDI4500BLQ</p> <p>JBLHDI4500GRO</p> <p>JBLHDI4500WAL</p>	<b>1.785 €</b>
HDI-1600	<p>2-Way Bookshelf Loudspeaker</p> <ul style="list-style-type: none"> <li>• 1" Teonex Compression Driver Tweeter</li> <li>• 6.5" black aluminum cone, cast-frame woofer</li> <li>• High-Definition Imaging (HDI™) waveguide</li> <li>• Dual sets of gold-plated binding posts</li> <li>• Crossover frequency: 1900 Hz</li> <li>• Sensitivity (2.83V @ 1M) 85dB</li> <li>• Nominal impedance: 4Ω</li> <li>• Recommended amplifier power: 15-200 W</li> <li>• Frequency response: 40 Hz – 30 kHz</li> <li>• Three finishes available: Black Lacquer, Grey Oak and Walnut</li> <li>• Dimensions (H x W x D): 14.57" x 9.06" x 11.6"</li> <li>• Weight: 21.96 lbs</li> </ul>	<p>JBLHDI1600BLQ</p> <p>JBLHDI1600GRO</p> <p>JBLHDI1600WAL</p>	<b>1.830 € / pair</b>

# JBL PREMIUM LOUDSPEAKERS

## HDI Series (cont.)



Model Name	Description	Material Number	MSRP
HDI-1200P	<p>12" Powered Subwoofer</p> <ul style="list-style-type: none"> <li>• 12" black aluminum cone, cast-frame woofer</li> <li>• 1000 W amplifier system</li> <li>• Bass-reflex design with rear-firing port</li> <li>• Recommended amplifier power: 1000 W rms</li> <li>• Crossover frequency: 50 Hz – 150 Hz (variable) 24dB/octave</li> <li>• Frequency response: 28 Hz – 150 Hz</li> <li>• Three finishes available: Black Lacquer, Grey Oak and Walnut</li> <li>• Power requirements: 100V – 240V 50/60 Hz</li> <li>• Dimensions: (H x W x D): 16.95" x 16.3" x 17.77"</li> <li>• Weight: 70.8 lbs</li> </ul>	<p>JBLHDI1200PBLQEU</p> <p>JBLHDI1200PGROEU</p> <p>JBLHDI1200PWALEU</p>	<b>3.000 €</b>
HDIFSStands	<p>JBL HDI Series floor stands. Accessory floor stands for HDI-1600</p> <ul style="list-style-type: none"> <li>• Designed to perfectly match the HDI-1600</li> <li>• Black gloss painted MDF base and includes carpet spikes</li> <li>• Anodized black aluminum column, with same gently curved sides as HDI-1600</li> <li>• Internal and external speaker cable routing options</li> <li>• Packed and sold in pairs</li> </ul>	JBLHDIFSBLK	<b>550 € / pair</b>

# JBL PREMIUM LOUDSPEAKERS

## SA750 Integrated Amplifier



Model Name	Description	Material Number	MSRP
SA750	<p>Streaming Integrated Stereo Amplifier – Anniversary Edition</p> <ul style="list-style-type: none"> <li>• Frequency Response: 20Hz – 20kHz ± 1dB</li> <li>• Nominal Sensitivity: 1V</li> <li>• Input Impedance: 10kΩ</li> <li>• Power output both channels driven: 120W into 8Ω, 220W into 4Ω</li> <li>• Maximum Input: 6Vrms</li> <li>• Total harmonic distortion + noise: 0.002%</li> <li>• Signal/Noise ratio (A-wtd) 50W, ref. 1V input: 20dB</li> <li>• Mains Voltage: 110-120V or 220-240V, 50-60Hz</li> <li>• Maximum Power Consumption: 800W</li> <li>• Product Dimensions (WxHxD, including feet, control knob, and speaker terminals): 449 x 114 x 327mm</li> <li>• Product Weight: 12kg</li> <li>• Shipping Weight: 14kg</li> </ul>	JBLSA750EU	3.525 €

## Terms and Conditions of Sale

**THIS PRICE LIST CANCELS ALL PREVIOUS LISTS AND IS VALID UNTIL FURTHER NOTICE.**

**ALL PRICES, SPECIFICATIONS, APPEARANCE, and TERMS AND CONDITIONS OF SALE ARE SUBJECT TO CHANGE WITHOUT NOTICE. E&OE**

**PRICES EFFECTIVE October 2021.**



HARMAN Luxury Audio Group  
The West Wing, Stirling House,  
Waterbeach, Cambridge.  
CB25 9PB  
Phone: +44 (0)1223 203200  
Email: [luxurysupport@harman.com](mailto:luxurysupport@harman.com)

JBL and JBL Synthesis are trademarks of HARMAN International Industries, Incorporated, registered in the United States and/or other countries. Features, specifications and appearance are subject to change without notice.

© 2021 HARMAN International Industries, Incorporated. All rights reserved.