



HARMAN LUXURY AUDIO

RETAIL PRICE LIST

Table of Contents

| | |
|--|-----------|
| PerformaBe | 3 |
| Performa3 | 5 |
| Concerta2 | 7 |
| Special Application In-Ceiling Loudspeakers | 9 |
| 6 1/2” In-Ceiling Loudspeakers | 10 |
| 6 1/2” Dual Tweeter In-Ceiling Loudspeakers | 12 |
| 8” In-Ceiling Loudspeakers | 13 |
| Special Application In-Wall Loudspeakers | 15 |
| 6 1/2” In-Wall Loudspeakers | 16 |
| 8” In-Wall Loudspeakers | 18 |
| 9” In-Wall Loudspeakers | 19 |
| In-Wall Subwoofer System | 20 |
| Extreme Climate Loudspeakers | 21 |
| Terms and Conditions | 23 |



| Model Name | Description | Material Number | MSRP |
|------------|---|---|-----------------|
| F328Be | <p>3-way Floorstanding Loudspeaker</p> <ul style="list-style-type: none"> • Three 8" Deep Ceramic Composite (DCC) aluminum cone woofers with cast frames • 5.25" DCC aluminum cone midrange with cast frame • 1" Beryllium dome tweeter with acoustic lens waveguide • Recommended amplifier power: 50 - 400 Watts • Nominal impedance: 8 ohms • Loudspeaker Sensitivity (2.83 V/1m): 91dB • Frequency Response: 26Hz - 40kHz (-6dB) • Crossover frequencies: 240Hz, 2.1kHz • Dimensions (H x W x D): 50.9 x 13.5 x 17.6" (1294 x 341.3 x 448.5mm) • Weight: 90 lbs | <p>REVF328BEBLK (black gloss) UPC: 050667374617</p> <p>REVF328BEWHT (white gloss) UPC: 050667374624</p> <p>REVF328BEWAL (walnut) UPC: 050667374631</p> <p>REVF328BESIL (silver) UPC: 050667374648</p> | 19.950 € |
| F228Be | <p>3-way Floorstanding Loudspeaker</p> <ul style="list-style-type: none"> • Dual 8" (200mm) Deep Ceramic Composite (DCC) aluminum cone woofers with cast frames • 5.25" (130mm) DCC aluminum cone midrange with cast frame • 1" Beryllium dome tweeter with acoustic lens waveguide • Recommended Amplifier Power: 50 – 350 Watts • Nominal Impedance: 8 ohms • Loudspeaker Sensitivity (2.83 V/1m): 90dB • Frequency Response: 33Hz - 40kHz (-6dB) • Crossover Frequency: 260Hz; 2.1kHz • Dimensions (H x W x D): 46.5 x 11.8 x 13.2" (1181 x 302 x 335mm) • Weight: 82 lbs (37.2kg) • Packaged dimensions (H x W x D): 52.8 x 19.5 x 23.7" (1340 x 495 x 603mm) • Packaged weight: 112 lbs (50.9 kg) • Inputs: Dual gold-plated binding posts with shorting straps | <p>REVF228BEBLK (black gloss) UPC: 050667372002</p> <p>REVF228BEWHT (white gloss) UPC: 050667372019</p> <p>REVF228BEWAL (walnut) UPC: 050667372026</p> <p>REVF228BESIL (silver) UPC: 050667372033</p> | 11.860 € |
| F226Be | <p>3-way Dual 6.5" Floorstanding Loudspeaker</p> <ul style="list-style-type: none"> • Two 6.5" (165mm) Deep Ceramic Composite aluminum cone with cast frame woofers • 5.25" (130mm) Deep Ceramic Composite aluminum cone midrange • 1" (25mm) Beryllium dome tweeter • Recommended Amplifier Power: 50-200 Watts • Frequency Response: 44Hz - 40kHz (-6dB) • Nominal Impedance: 8 ohms • Loudspeaker Sensitivity (2.83V/1m): 90dB • Crossover Frequencies: 260Hz; 2.1kHz • Dimensions (H x W x D): 41.3" x 9.8" x 13.7" (1050mm x 249mm x 347mm) • Weight: 58.8 lbs (26.8kg) | <p>REVF226BEBLK (black gloss) UPC: 050667374051</p> <p>REVF226BEWHT (white gloss) UPC: 050667374068</p> <p>REVF226BEWAL (walnut) UPC: 050667374075</p> <p>REVF226BESIL (silver) UPC: 050667374082</p> | 9.340 € |

PERFORMA⁴ Be™ LOUDSPEAKER SERIES



| Model Name | Description | Material Number | MSRP |
|------------|--|---|---------|
| M126Be | <p>2-way Bookshelf Loudspeaker</p> <ul style="list-style-type: none"> • 6.5" (165mm) Deep Ceramic Composite (DCC) aluminum cone woofer with cast frame • 1" (25mm) Beryllium dome tweeter with acoustic lens waveguide • Recommended Amplifier Power: 50 – 150 Watts • Nominal Impedance: 8 ohms • Loudspeaker Sensitivity (2.83 V/1m): 86dB • Frequency Response: 46Hz - 40kHz (-6dB) • Crossover Frequency: 1.7kHz • Dimensions (H x W x D): 15.2 x 8.3 x 10.3" (386 x 211 x 262mm) • Weight: 22 lbs (9.97kg) • Packaged dimensions (H x W x D): 19 x 12.3 x 16.3" (483 x 311 x 413mm) • Packaged weight: 26 lbs (11.6 kg) • Inputs: Gold-plated binding posts | <p>REVM126BEBLK (black gloss) UPC: 050667371968</p> <p>REVM126BEWHT (white gloss) UPC: 050667371975</p> <p>REVM126BEWAL (walnut) UPC: 050667371982</p> <p>REVM126BESIL (silver) UPC: 050667371999</p> | 4.670 € |
| C426Be | <p>3-way Quadruple 6.5" Center Channel Loudspeaker</p> <ul style="list-style-type: none"> • Four 6.5" (165mm) Deep Ceramic Composite aluminum cone with cast frame woofers • 5.25" (130mm) Deep Ceramic Composite aluminum cone midrange • 1" (25mm) Beryllium dome tweeter • Recommended Amplifier Power: 50-300 Watts RMS • Frequency Response: 38Hz - 40kHz (-6dB) • Nominal Impedance: 8 ohms • Loudspeaker Sensitivity (2.83V/1m): 90dB • Crossover Frequencies: 210Hz; 2.1kHz • Dimensions (H x W x D): 10.4" x 38.6" x 14.0" (263mm x 979.7mm x 358mm) • Weight: 61lbs (27.7kg) | <p>REVC426BEBLK (black gloss) UPC: 050667374501</p> <p>REVC426BEWHT (white gloss) UPC: 050667374518</p> <p>REVC426BEWAL (walnut) UPC: 050667374525</p> <p>REVC426BESIL (silver) UPC: 050667374532</p> | 5.390 € |





PERFORMA³ LOUDSPEAKER SERIES



| Model Name | Description | Material Number | MSRP |
|------------|---|---|---------|
| F208 | <p>3-Way Floorstanding Tower Loudspeaker</p> <ul style="list-style-type: none"> • Dual 8" (20 cm) Aluminum Cone, Cast- frame Woofers • 5.25" (13.3 cm) Aluminum Cone, Cast- frame Midrange • 1" (2.5 cm) Aluminum Tweeter with Acoustic Lens Waveguide • Recommended amplifier power range: 50 – 350 watts • Low-frequency extension: 23Hz (–10dB); 27Hz (–6dB); 31Hz (–3dB) • Nominal impedance: 8 ohms • Sensitivity (2.83V/1m): 88.5dB • Enclosure type: Bass-reflex via front-mounted port • Controls: Low-frequency contour; high-frequency level • Inputs: Dual gold-plated binding posts with shorting straps • Dimensions (H x W x D): 46.5" x 11.8" x 14.8" (118.2 cm x 30 cm x 37.5 cm) • Weight: 80 lb (36 kg) / Packaged weight: 87 lb (39.6 kg) • Packaged dimensions (H x W x D): 50.2" x 17.7" x 21.5" (127.5 cm x 45 cm x 54.5 cm) • Piano Black or High Gloss Walnut | <p>F208 BK (Piano Black) UPC: 848592000110</p> <p>F208 WA (Walnut) UPC: 848592000134</p> | 5.750 € |
| F206 | <p>3-Way Floorstanding Tower Loudspeaker</p> <ul style="list-style-type: none"> • Dual 6.5" (16.5 cm) Aluminum Cone, Cast- frame Woofers • 5.25" (13.3 cm) Aluminum Cone, Cast- frame Midrange • 1" (2.5 cm) Aluminum Tweeter with Acoustic Lens Waveguide • Recommended amplifier power range: 50 – 200 watts • Low-frequency extension: 30Hz (–10dB); 34Hz (–6dB); 42Hz (–3dB) • Nominal impedance: 8 ohms • Sensitivity (2.83V/1m): 88dB • Enclosure type: Bass-reflex via front-mounted port • Inputs: Gold-plated binding posts • Dimensions (H x W x D): 41.4" x 9.8" x 13.7" (105.1 cm x 24.9 cm x 34.7 cm) • Weight: 58 lb (26 kg) / Packaged weight: 65 lb (29.4 kg) • Packaged dimensions (H x W x D): 45.3" x 14.2" x 21.1" (115 cm x 45 cm x 53.5 cm) • Piano Black, Piano White, or High Gloss Walnut | <p>F206 BK (Piano Black) UPC: 848592000080</p> <p>F206 WA (Walnut) UPC: 848592000103</p> <p>F206 WH (White) UPC: 848592000073</p> | 4.130 € |
| M106 | <p>2-Way Bookshelf Monitor Loudspeaker</p> <ul style="list-style-type: none"> • 6.5" (16.5 cm) Aluminum Cone, Cast-frame Woofer • 1" (2.5 cm) Aluminum Tweeter with Acoustic Lens Waveguide • Recommended amplifier power range: 50 – 150 watts • Low-frequency extension: 39Hz (–10dB); 54Hz (–6dB); 59Hz (–3dB) • Nominal impedance: 8 ohms • Sensitivity (2.83V/1m): 87dB • Enclosure type: Bass-reflex via rear-mounted port • Inputs: Gold-plated binding posts • Dimensions (H x W x D): 15" x 8.3" x 11" (38.1 cm x 21 cm x 27.8 cm) • Weight: 19 lb (8 kg) / Packaged weight: 22 lb (9.8 kg) • Packaged dimensions (H x W x D): 18.9" x 12.2" x 16.1" (48 cm x 31 cm x 41 cm) • Piano Black or High Gloss Walnut | <p>M106 BK (Piano Black) UPC: 848592000042</p> <p>M106 WA (Walnut) UPC: 848592000066</p> | 2.340 € |
| M Stand | <p>Optional Floor Pedestal for M105/M106</p> <ul style="list-style-type: none"> • Packed and sold in pairs • Dimensions (H x W x D): 25" x 9.4" x 11.5" (63.5 cm x 23.8 cm x 29.1 cm) • Weight: 8 lb (4 kg) / Packaged weight: 22 lb (10.1 kg) • Packaged dimensions (H x W x D): 27.2" x 13" x 15.6" (69 cm x 33 cm x 39.5 cm) • Black or White Finish | <p>M STAND BK (Piano Black) UPC: 848592000257</p> <p>M STAND WH (White) UPC: 848592000455</p> | 540 € |

PERFORMA³ LOUDSPEAKER SERIES



| Model Name | Description | Material Number | MSRP |
|---|---|---|---------|
|  M105 | 2-Way Bookshelf Monitor Loudspeaker <ul style="list-style-type: none"> • 5.25" (13.3 cm) Aluminum Cone, Cast- frame Woofer • 1" (2.5 cm) Aluminum Tweeter with Acoustic Lens Waveguide • Recommended amplifier power range: 50 – 120 watts • Low-frequency extension: 44Hz (–10dB); 56Hz (–6dB); 60Hz (–3dB) • Nominal impedance: 8 ohms • Sensitivity (2.83V/1m): 86dB • Enclosure type: Bass-reflex via rear-mounted port • Inputs: Gold-plated binding posts • Dimensions (H x W x D): 14" x 7.9" x 9.8" (35.6 cm x 20 cm x 24.8 cm) • Weight: 16 lb (7 kg) / Packaged weight: 18 lb (8.4 kg) • Packaged dimensions (H x W x D): 18.1" x 12.2" x 15.6" (46 cm x 31 cm x 39.5 cm) • Piano Black, Piano White, or High Gloss Walnut | M105 BK (Piano Black) UPC: 848592000011 M105 WA (Walnut) UPC: 848592000035 M105 WH (White) UPC: 848592000004 | 1.760 € |
|  C208 | 3-Way Center Channel Loudspeaker <ul style="list-style-type: none"> • Dual 8" (20 cm) Aluminum Cone, Cast- frame Woofers • 4" (10 cm) Aluminum Cone, Cast-frame Midrange • 1" (2.5 cm) Aluminum Tweeter with Acoustic Lens Waveguide • Recommended amplifier power range: 50 – 350 watts • Low-frequency extension: 34Hz (–10dB); 41Hz (–6dB); 50Hz (–3dB) • Nominal impedance: 8 ohms • Sensitivity (2.83V/1m): 89dB • Enclosure type: Sealed • Controls: Low-frequency contour; high-frequency level • Inputs: Dual gold-plated binding posts with shorting straps • Dimensions (H x W x D): 11.8" x 28.9" x 13.8" (30 cm x 73.5 cm x 35 cm) • Weight: 52 lb (23 kg) / Packaged weight: 55 lb (24.9 kg) • Packaged dimensions (H x W x D): 15.9" x 32.3" x 20.5" (40.5 cm x 82 cm x 52 cm) • Piano Black or High Gloss Walnut | C208 BK (Piano Black) UPC: 848592000219 C208 WA (Walnut) UPC: 848592000233 | 2.335 € |
|  C Stand | Optional Floor Pedestal for C205/C208 <ul style="list-style-type: none"> • Dimensions (H x W x D): 10.8" x 21.4" x 11.9" (27.5 cm x 54.4 cm x 30.1 cm) • Net Weight: 15 lb (7 kg) • Black or White Finish | C STAND BK (Piano Black) UPC: 848592000264 C STAND WH (White) UPC: 848592000462 | 280 € |
|  C205 | 2-Way Center Channel Loudspeaker <ul style="list-style-type: none"> • Dual 5.25" (13.3 cm) Aluminum Cone, Cast- frame Woofers • 1" (2.5 cm) Aluminum Tweeter with Acoustic Lens Waveguide • Recommended amplifier power range: 50 – 120 watts • Low-frequency extension: 46Hz (–10dB); 62Hz (–6dB); 80Hz (–3dB) • Nominal impedance: 8 ohms • Sensitivity (2.83V/1m): 89dB • Crossover frequencies: 1.7kHz • Enclosure type: Sealed • Inputs: Gold-plated binding posts • Dimensions (H x W x D): 7.9" x 21" x 11.5" (20 cm x 53.2 cm x 29.2 cm) • Weight: 26 lb (12 kg) / Packaged weight: 29 lb (13.3 kg) • Packaged dimensions (H x W x D): 12.2" x 24" x 17.9" (310 x 610 x 455mm) • Piano Black, Piano White, or High Gloss Walnut | C205 BK (Piano Black) UPC: 848592000189 C205 WA (Walnut) UPC: 848592000202 C205 WH (White) UPC: 848592000172 | 1.170 € |

PERFORMA³ LOUDSPEAKER SERIES



| Model Name | Description | Material Number | MSRP |
|------------|--|---|---------|
| F35 | <p>2½-Way Triple 5.25" Floorstanding Loudspeaker</p> <ul style="list-style-type: none"> • HF Drive Component: 1" Aluminum Tweeter with Acoustic Lens Waveguide • LF/MF Drive Component: 3 x 5.25" Aluminum Cone Woofers • Crossover Frequency: 575Hz, 1.8kHz • Input Connections: Five-way binding posts • Sensitivity (2.83V @ 1M): 90dB • Nominal Impedance: 6 Ohms • Recommended Amplifier Power: 30-180W • Dimension(H x W x D): 40.25" x 8.42" x 12.2" • Weight: 41 lbs • Packaged dimensions (H x W x D): 13.2" x 45.5" x 17.7" (335 x 1155 x 450mm) • Packaged weight: 52 lb (23.6 kg) | <p>F35BK (Black Gloss) UPC: 050036327152</p> <p>F35WH (White Gloss) UPC: 050036327206</p> | 2.150 € |
| M16 | <p>2-Way 6.5" Bookshelf Loudspeaker</p> <ul style="list-style-type: none"> • HF Drive Component: 1" Aluminum Tweeter with Acoustic Lens Waveguide • LF/MF Drive Component: 6.5" Aluminum Cone Woofer • Crossover Frequency: 2.1kHz • Input Connections: Five-way binding posts • Sensitivity (2.83V @ 1M): 86dB • Nominal impedance: 6 Ohms • Recommended Amplifier Power: 50-120W • Dimension(H x W x D): 14.75" x 8.6" x 10.75" • Weight: 16 lbs • Packaged dimensions (H x W x D): 12.4" x 19.3" x 15.4" (315 x 490 x 390mm) • Packaged weight: 20 lb (9.2 kg) | <p>M16BK (Black Gloss) UPC: 050036327145</p> <p>M16WH (White Gloss) UPC: 050036327190</p> | 1.260 € |
| M16 Stand | <p>Optional Floor Pedestal for M16</p> <ul style="list-style-type: none"> • Dimensions (H x W x D): 25.5" x 9.37" x 11.4" • Weight: 37 lbs / Packaged weight: 40 lb (18 kg) • Packaged dimensions (H x W x D): 12.8" x 5" x 24.4" (324 x 127 x 620mm) • Black Finish • Packed and sold in pairs | <p>M16 STAND UPC: 050036327305</p> | 335 € |
| C25 | <p>2-Way Dual 5.25" Center Channel Loudspeaker</p> <ul style="list-style-type: none"> • HF Drive Component: 1" Aluminum Tweeter with Acoustic Lens Waveguide • LF/MF Drive Component: Dual 5.25" Aluminum Cone Woofers • Crossover Frequency: 2.1kHz • Input Connections: Five-way binding posts • Sensitivity (2.83V @ 1M): 89dB • Nominal Impedance: 6 Ohms • Recommended Amplifier Power: 40-120W • Dimensions (H x W x D): 7.25 x 19.45 x 10.1" • Weight: 20 lbs • Packaged dimensions (H x W x D): 11.5" x 24.1" x 15" (292 x 612 x 380mm) • Packaged weight: 24 lb (11 kg) | <p>C25BK UPC: 50036327176</p> <p>C25WH UPC: 50036327220</p> | 825 € |
| C25 Stand | <p>Optional Floor Pedestal for C25</p> <ul style="list-style-type: none"> • Dimensions (H x W x D): 12.0" x 19.0" x 11.4" • Weight: 21 lbs • Packaged dimensions (H x W x D): 10.2" x 5.2" x 21.6" (260 x 132 x 548mm) • Packaged weight: 21 lb (9.5 kg) • Black Finish | <p>C25 STAND UPC: 50036327312</p> | 225 € |

PERFORMA³ LOUDSPEAKER SERIES



| Model Name | Description | Material Number | MSRP |
|------------|--|---|---------|
| B10 | <p>800 Watt 10" Powered Subwoofer</p> <ul style="list-style-type: none"> • LF/MF Drive Components: 10" Coated Fiber-Composite Cone, Cast-Frame Woofer • Crossover Frequency: Variable 10-150Hz • Input Connections: L/R Stereo RCA Input • Recommended Amplifier Power: 800W Class D Amplifier • Dimensiona (H x W x D): 16.45" x 14.85" x 15.45" • Weight: 53 lbs • Packaged dimensions (H x W x D): 19" x 20.7" x 19.8" (482 x 526 x 502mm) • Packaged weight: 54 lb (24.5 kg) | <p>B10BK (Black Gloss) UPC: 050036327244</p> <p>B10WH (White Gloss) UPC: 050036327251</p> <p>B10BKEU (230V) UPC: 050036327268</p> <p>B10WHEU (230V) UPC: 050036327275</p> | 1.795 € |

IN-CEILING & IN-WALL ARCHITECTURAL LOUDSPEAKERS



Special Application In-Ceiling and LCR loudspeakers



| Model Name | Description | Material Number | MSRP |
|---------------------|--|------------------------------------|-------|
| C540 | <p>4" Micro-Ceramic Composite (MCC) Cone, Cast-Aluminum Frame Woofer</p> <ul style="list-style-type: none"> • 1" aluminum dome tweeter with waveguide • Mounting depth: 3.3" (8.4 cm) • Weight: 1.5 lb (0.7 kg) / Shipping weight: 1.9 lb (0.9 kg) • Cutout dimensions (dia.): 3.5" (8.9 cm) • Includes both round and square zero-bezel magnetic grilles • Round grille finished dimension (dia.): 4.4" (11.2 cm) • Square grille finished dimensions (h x w): 4.4" x 4.4" (11.2 cm x 11.2 cm) • Roller Lock tool-free installation mechanism • Recommended amplifier power range: 10- 80 watts • Nominal impedance: 8 ohms • Sensitivity (2.83V/1m): 85 dB • Frequency Range -3 dB from 180Hz-20kHz ; -10dB from 150-30kHz • Compatible with wall material thickness range: 0.5" – 0.9" (1.3 cm – 2.3 cm) | REVEL C540 | 235 € |
| Fire-Rated Back-Box | Fire (1 hour) Rated Steel Backbox for C540 In-ceiling Loudspeaker | FBB4C | 125 € |
| C763L | <p>7.8" x 3.4" Micro-Ceramic Composite (MCC) Cone, Diaphragm Flat-Panel Woofer</p> <ul style="list-style-type: none"> • Two 3.5" micro-ceramic composite (MCC) cone, cast-aluminum frame high-output midranges • 1" aluminum high-output tweeter with waveguide • In-ceiling LCR or Surround Speaker • 3-position HF level control • LF boundary compensation • Mounting depth: 5.7" (14.5 cm) • Weight: 4 lb (1.8 kg) / Shipping weight: 5.2 lb (2.4 kg) • Cutout dimensions (dia.): 11.3" (28.7 cm) • Includes both round and square zero-bezel magnetic grilles • Round grille finished dimension (dia.): 12.5" (31.8 cm) • Square grille finished dimensions (h x w): 12.5" x 12.5" (31.8 cm x 31.8 cm) • Nominal impedance: 8 ohms • Recommended amplifier power range: 10- 200 watts • Sensitivity (2.83V/1m): 86 dB • Frequency Range -3 dB from 80Hz-28kHz; -10dB from 72 -35kHz • C-2 fastening mechanism • Compatible with wall material thickness range: 0.5" – 2.0" (1.3 cm – 5.0 cm) | <p>C763L UPC: 848592000318</p> | 885 € |
| Fire-Rated Back-Box | Fire (1 hour) and Plenum Rated Steel Backbox for C763L In-ceiling Loudspeaker | FBB10C | 155 € |

IN-CEILING & IN-WALL ARCHITECTURAL LOUDSPEAKERS



6 1/2" In-Ceiling Loudspeakers



| Model Name | Description | Material Number | MSRP |
|------------|--|---------------------------|-------|
| C263 | <p>6 1/2" Aluminum Cone, Cast-polymer Frame Woofer</p> <ul style="list-style-type: none"> • 1" Aluminum Dome Tweeter with Waveguide • Mounting Depth: 4.8" (12.2 cm) • Weight: 3.1 lb (1.41 kg) / Shipping Weight: 4.6 lb (2.1 kg) • Includes a round zero-bezel magnetic grille • Round Grille Finished Dimension (Dia.): 9.1" (23.1 cm) • Cutout Dimensions (Dia.): 8" (20.3 cm) • Nominal impedance: 8 ohms • Recommended amplifier power range: 10- 100 watts • Sensitivity (2.83V/1m): 86 dB • Frequency Range -3 dB from 50-18 kHz; -10dB from 36-20 kHz | C263 | 175 € |
| C363 | <p>6 1/2" Micro-Ceramic Composite (MCC) Cone, Cast-Polymer Frame Woofer</p> <ul style="list-style-type: none"> • 1" aluminum dome swiveling tweeter with waveguide • Mounting depth: 4.8" (12.2 cm) • Weight: 1.6 lb (0.8 kg) / Shipping weight: 2.4 lb (1.1 kg) • Cutout dimensions (dia.): 8" (20.3 cm) • Includes both round and square zero-bezel magnetic grilles • Nominal impedance: 8 ohms • Recommended amplifier power range: 10- 100 watts • Sensitivity (2.83V/1m): 86 dB • Frequency Range -3 dB from 50-18 kHz; -10dB from 36-20 kHz • Round grille finished dimension (dia.): 9.1" (23.1 cm) • Square grille finished dimensions (H x W): 9.1" x 9.1" (23 cm x 23 cm) | C363 UPC: 848592000028 | 295 € |
| C563 | <p>6 1/2" Micro-Ceramic Composite (MCC) Cone, Cast-Aluminum Frame Woofer</p> <ul style="list-style-type: none"> • 1" aluminum dome swiveling tweeter with waveguide • 3-position HF level control • Mounting depth: 4.9" (12.5 cm) • Weight: 2 lb (0.9 kg) /Shipping weight: 2.7 lb (1.2 kg) • Cutout dimensions (dia.): 8" (20.3 cm) • Nominal impedance: 8 ohms • Recommended amplifier power range: 10- 130 watts • Sensitivity (2.83V/1m): 88 dB • Frequency Range -3 dB from 50Hz-25kHz; -10dB from 35-30kHz • Includes both round and square zero-bezel magnetic grilles • Round grille finished dimension (dia.): 9.1" (23.1 cm) • Square grille finished dimensions (H x W): 9.1" x 9.1" (23.1 cm x 23.1 cm) | C563 UPC: 848592000097 | 415 € |

IN-CEILING & IN-WALL ARCHITECTURAL LOUDSPEAKERS



6 1/2" In-Ceiling Loudspeakers (cont.)



| Model Name | Description | Material Number | MSRP |
|--|---|-----------------------------------|--------------|
| C763 | <p>6 1/2" Micro-Ceramic Composite Cone (MCC), Cast-Aluminum Frame High-Output Woofer</p> <ul style="list-style-type: none"> • 1" aluminum dome swiveling high-output tweeter with waveguide • 3-position HF level control • LF boundary compensation • Mounting depth: 4.9" (12.5 cm) • Weight: 2.4 lb (1.1 kg) / Shipping weight: 3.2 lb (1.5 kg) • Cutout dimensions (dia.): 8" (20.3 cm) • Nominal impedance: 8 ohms • Recommended amplifier power range: 10- 140 watts • Sensitivity (2.83V/1m): 88 dB • Frequency Range -3 dB from 45Hz-28kHz; -10dB from 30-35kHz • Includes both round and square zero-bezel magnetic grilles • Round grille finished dimension (dia.): 9.1" (23.1 cm) • Square grille finished dimensions (H x W): 9.1" x 9.1" (23.1 cm x 23.1 cm) | <p>C763 UPC: 848592000127</p> | <p>590 €</p> |
| Fire Rated Back box (All Cx63 models) | Fire (1 hour) and Plenum Rated Steel Backbox for all 6 1/2" Cx63 In-ceiling Loudspeakers | FBB6C | 125 € |

IN-CEILING & IN-WALL ARCHITECTURAL LOUDSPEAKERS



6 1/2" Tweeter In-Ceiling Loudspeakers



| Model Name | Description | Material Number | MSRP |
|--|--|-----------------------------|-------|
| C363DT | <p>6 1/2" Micro-Ceramic Composite (MCC) Cone, Cast-polymer Frame Woofer</p> <ul style="list-style-type: none"> • Two 1" aluminum dome tweeters with waveguides • Mounting depth: 4.8" (12.2 cm) • Weight: 1.9 lb (0.9 kg) / Shipping Weight: 2.6 lb (1.2 kg) • Cutout dimensions (dia.): 8" (20.3 cm) • Nominal impedance: 8 ohms • Recommended amplifier power range: 10- 120 watts (Per Channel) • Sensitivity (2.83V/1m): 88 dB • Frequency Range -3 dB from 55Hz-22kHz; -10dB from 40-30kHz • Includes both round and square zero-bezel magnetic grilles • Round grille finished dimension (dia.): 9.1" (23.1 cm) • Square grille finished dimensions (H x W): 9.1" x 9.1" (23.1 cm x 23.1 cm) • C-2 fastening mechanism • Compatible with wall material thickness range: 0.5" – 2.0" (1.3 cm – 5.0 cm) | C363DT UPC: 848592000059 | 355 € |
| C563DT | <p>6 1/2" Micro-Ceramic Composite (MCC) Cone, Cast-Aluminum Frame Woofer</p> <ul style="list-style-type: none"> • Two 1" aluminum dome tweeters with waveguides • 3-position HF level control • Mounting depth: 4.9" (12.5 cm) • Weight: 2.2 lb (1 kg) / Shipping weight: 3 lb (1.4 kg) • Cutout dimensions (dia.): 8" (20.3 cm) • Nominal impedance: 8 ohms • Recommended amplifier power range: 10- 130 watts (Per Channel) • Sensitivity (2.83V/1m): 88 dB • Frequency Range -3 dB from 55Hz-28kHz; -10dB from 30-35kHz • Includes both round and square zero-bezel magnetic grilles • Round grille finished dimension (dia.): 9.1" (23.1 cm) • Square grille finished dimensions (H x W): 9.1" x 9.1" (23.1 cm x 23.1 cm) • C-2 fastening mechanism • Compatible with wall material thickness range: 0.5" – 2.0" (1.3 cm – 5.0 cm) | C563DT UPC: 848592000158 | 470 € |
| Fire Rated Back box (All Cx63 models) | Fire (1 hour) and Plenum Rated Steel Backbox for all 6 1/2" Cx63 In-ceiling Loudspeakers | FBB6C | 125 € |

IN-CEILING & IN-WALL ARCHITECTURAL LOUDSPEAKERS



8" In-Ceiling Loudspeakers



| Model Name | Description | Material Number | MSRP |
|------------|--|---------------------------|-------|
| C283 | <p>8" Aluminum Cone, Cast-polymer Frame Woofer</p> <ul style="list-style-type: none"> • 1" Aluminum Dome Tweeter with Waveguide • Mounting depth: 5.2" (13.2 cm) • Weight: 3.9 lb (1.8 kg) / Shipping Weight: 5.9 lb (2.7 kg) • Includes round zero-bezel magnetic grille • Round grille finished dimension (dia.): 10.7" (27.2 cm) • Cutout dimensions (dia.): 9.6" (24.4 cm) • Nominal impedance: 8 ohms • Recommended amplifier power range: 10- 100 watts • Sensitivity (2.83V/1m): 87 dB • Frequency Range -3 dB from 36-18 kHz; -10dB from 28-20 kHz | C283 | 235 € |
| C383 | <p>8" Micro-Ceramic Composite (MCC) Cone, Cast-Polymer Frame Woofer</p> <ul style="list-style-type: none"> • 1" aluminum dome swiveling tweeter with waveguide • Mounting depth: 5.2" (13.2 cm) • Weight: 2.1 lb (1 kg) / Shipping weight: 3.1 lb (1.4 kg) • Cutout dimensions (dia.): 9.6" (24.4 cm) • Nominal impedance: 8 ohms • Recommended amplifier power range: 10- 125 watts • Sensitivity (2.83V/1m): 87 dB • Frequency Range -3 dB from 45Hz-22kHz; -10dB from 35-30kHz • Includes both round and square zero-bezel magnetic grilles • Round grille finished dimension (dia.): 10.7" (27.2 cm) • Square grille finished dimensions (h x w): 10.7" x 10.7" (27.2 cm x 27.2 cm) | C383 UPC:848592000196 | 415 € |
| C583 | <p>8" Micro-Ceramic Composite (MCC) Cone, Cast-Aluminum Frame Woofer</p> <ul style="list-style-type: none"> • 1" aluminum dome swiveling tweeter with waveguide • 3-position HF level control • Mounting depth: 5.2" (13.2 cm) • Weight: 2.8 lb (1.3 kg) / Shipping weight: 3.8 lb (1.7 kg) • Cutout dimensions (dia.): 9.6" (24.4 cm) • Nominal impedance: 8 ohms • Recommended amplifier power range: 10- 135 watts • Sensitivity (2.83V/1m): 88 dB • Frequency Range -3 dB from 45Hz-25kHz; -10dB from 30-30kHz • Includes both round and square zero-bezel magnetic grilles • Round grille finished dimension (dia.): 10.7" (27.2 cm) • Square grille finished dimensions (h x w): 10.7" x 10.7" (27.2 cm x 27.2 cm) | C583 UPC: 848592000226 | 530 € |

IN-CEILING & IN-WALL ARCHITECTURAL LOUDSPEAKERS



8" In-Ceiling Loudspeakers (cont.)



| Model Name | Description | Material Number | MSRP |
|--|---|---------------------------|-------|
| C783 | 8" Micro-Ceramic Composite (MCC) Cone, Cast-Aluminum Frame High-Output Woofer <ul style="list-style-type: none"> • 1" aluminum dome swiveling high-output tweeter with waveguide • 3-position HF level control • LF boundary compensation • Mounting depth: 5.2" (13.2 cm) • Weight: 3.1 lb (1.4 kg) / Shipping weight: 4.1 lb (1.9 kg) • Cutout dimensions (dia.): 9.6" (24.4 cm) • Nominal impedance: 8 ohms • Recommended amplifier power range: 10- 150 watts • Sensitivity (2.83V/1m): 88 dB • Frequency Range -3 dB from 36Hz-28kHz; -10dB from 25-35kHz • Includes both round and square zero-bezel magnetic grilles • Round grille finished dimension (dia.): 10.7" (27.2 cm) • Square grille finished dimensions (h x w): 10.7" x 10.7" (27.2 cm x 27.2 cm) | C783 UPC: 848592000288 | 705 € |
| Fire Rated Back box (All Cx83 models) | Fire (1 hour) and Plenum Rated Steel Backbox for all 8" Cx83 In-ceiling Loudspeakers | FBB8C | 155 € |

IN-CEILING & IN-WALL ARCHITECTURAL LOUDSPEAKERS



Special Application In-Wall Loudspeakers



| Model Name | Description | Material Number | MSRP |
|--|---|------------------------------------|---------------------|
| W553L | <p>Two 5" Micro-Ceramic Composite (MCC) Cone, Cast-Aluminum Frame Woofers</p> <ul style="list-style-type: none"> • Can be mounted Vertical or Horizontal for L-C-R applications • 1" aluminum dome swiveling tweeter with waveguide • Nominal impedance: 8 ohms • Recommended amplifier power range: 10- 150 watts • Sensitivity (2.83V/1m): 91 dB • Frequency Range -3 dB from 50Hz-25kHz; -10dB from 35-35kHz • 3-position HF level control • Mounting depth: 2.9" (7.4 cm) • Weight: 6.6 lb / Shipping weight: 7.7 lb (3.5 kg) • Cutout dimensions (H x W): 14.1" x 6.4" (35.9 cm x 16.3 cm) • Includes zero-bezel magnetic grille • Grille finished dimension (H x W): 15.1" x 7.4" (38.4 cm x 18.8cm) • C-2 fastening mechanism • Compatible with wall material thickness range: 0.5" – 2.0" (1.3 cm – 5.0 cm) | <p>W553L UPC: 848592000479</p> | <p>530 €</p> |
| Fire Rated Back box (All Wx53 models) | <p>Fire (1 hour) and Plenum Rated Steel Backbox for W253L and W553L In-wall Loudspeaker</p> | <p>FBB55</p> | <p>155 €</p> |

IN-CEILING & IN-WALL ARCHITECTURAL LOUDSPEAKERS



6 1/2" In-Wall Loudspeakers



| Model Name | Description | Material Number | MSRP |
|------------|---|---------------------------|-------|
| W263 | 6 1/2" Aluminum Cone, Cast-Polymer Frame Woofer <ul style="list-style-type: none"> • 1" aluminum dome tweeter with waveguide • Mounting depth: 3.5" (8.8 cm) • Weight: 3.4 lb (1.5 kg) / Shipping weight: 4.9 lb (2.2 kg) • Includes zero-bezel magnetic grille • Grille finished dimension (H x W): 10.8" x 8.3" (27.3 cm x 21.1 cm) • Cutout dimensions (H x W): 9.8" x 7.3" (24.9 cm x 18.5 cm) • Nominal impedance: 8 ohms • Recommended amplifier power range: 10- 100 watts • Sensitivity (2.83V/1m): 88 dB • Frequency Range -3 dB from 50-18 kHz; -10dB from 35-20 kHz | W263 | 180 € |
| W363 | 6 1/2" Micro-Ceramic Composite (MCC) Cone, Cast-Polymer Frame Woofer <ul style="list-style-type: none"> • 1" aluminum dome swiveling tweeter with waveguide • Mounting depth: 3.6" (9.1 cm) • Weight: 3.8 lb (1.7 kg) / Shipping weight: 4.9 lb (2.2 kg) • Cutout dimensions (H x W): 9.8" x 7.3" (24.9 cm x 18.5 cm) • Includes zero-bezel magnetic grille • Grille finished dimension (H x W): 10.8" x 8.3" (27.3 cm x 21.1 cm) • Nominal impedance: 8 ohms • Recommended amplifier power range: 10- 120 watts • Sensitivity (2.83V/1m): 88 dB • Frequency Range -3 dB from 55Hz-22kHz; -10dB from 40-30kHz | W363 UPC: 848592000370 | 295 € |
| W563 | 6 1/2" Micro-Ceramic Composite (MCC) Cone, Cast-Aluminum Frame Woofer <ul style="list-style-type: none"> • 1" aluminum dome swiveling tweeter with waveguide • 3-position HF level control • Mounting depth: 3.7" (9.4 cm) • Weight: 4.4 lb (2 kg) / Shipping weight: 5.5 lb (2.5 kg) • Cutout dimensions (H x W): 9.8" x 7.3" (24.9 cm x 18.5 cm) • Includes zero-bezel magnetic grille • Grille finished dimension (H x W): 10.8" x 8.3" (27.3 cm x 21.1 cm) • Nominal impedance: 8 ohms • Recommended amplifier power range: 10- 130 watts • Sensitivity (2.83V/1m): 88 dB • Frequency Range -3 dB from 50Hz-25kHz; -10dB from 35-30kHz | W563 UPC: 848592000400 | 415 € |

IN-CEILING & IN-WALL ARCHITECTURAL LOUDSPEAKERS



6 1/2" In-Wall Loudspeakers (cont.)



| Model Name | Description | Material Number | MSRP |
|--------------------|---|----------------------|-------|
| W763 | 6 1/2" Micro-Ceramic Composite (MCC) Cone, Cast-Aluminum Frame High-Output Woofer <ul style="list-style-type: none"> • 1" aluminum dome swiveling high-output tweeter with waveguide • 3-position HF level control • LF boundary compensation • Mounting depth: 3.6" (9.1 cm) • Weight: 5.4 lb (2.5 kg) / Shipping weight: 6.5 lb (3.0 kg) • Cutout dimensions (H x W): 9.8" x 7.3" (24.9 cm x 18.5 cm) • Includes zero-bezel magnetic grille • Grille finished dimension (H x W): 10.8" x 8.3" (27.3 cm x 21.1 cm) • Nominal impedance: 8 ohms • Recommended amplifier power range: 10- 140 watts • Sensitivity (2.83V/1m): 89 dB • Frequency Range -3 dB from 45Hz-28kHz; -10dB from 30-35kHz | W763 848592000431 | 590 € |
| Fire rated Backbox | Fire (1 hour) and Plenum Rated Steel Backbox for Wx63 In-wall Loudspeaker | FBB6 | 100 € |

IN-CEILING & IN-WALL ARCHITECTURAL LOUDSPEAKERS



8" In-Wall Loudspeakers



| Model Name | Description | Material Number | MSRP |
|------------|--|---------------------------|-------|
| W283 | <p>8" Aluminum Cone, Cast-Polymer Frame Woofer</p> <ul style="list-style-type: none"> • 1" aluminum dome tweeter with waveguide • Mounting depth: 3.7" (9.4 cm) • Weight: 4.4 lb (2 kg) / Shipping weight: 6.3 lb (3 kg) • Cutout dimensions (H x W): 11.9" x 8.9" (30.3 cm x 22.7 cm) • Includes zero-bezel magnetic grille • Grille finished dimension (H x W): 12.9" x 9.9" (32.8 cm x 25.2 cm) • Nominal impedance: 8 ohms • Recommended amplifier power range: 10- 100 watts • Sensitivity (2.83V/1m): 88 dB • Frequency Range -3 dB from 37-18 kHz; -10dB from 29-20 kHz | W283 | 235 € |
| W383 | <p>8" Micro-Ceramic Composite (MCC) Cone, Cast- Polymer Frame Woofer</p> <ul style="list-style-type: none"> • 1" aluminum dome swiveling tweeter with waveguide • Mounting depth: 3.7" (9.4 cm) • Weight: 4.9 lb (2.2 kg) / Shipping weight: 6.3 lb (2.9 kg) • Cutout dimensions (H x W): 11.9" x 8.9" (30.3 cm x 22.7 cm) • Includes zero-bezel magnetic grille • Grille finished dimension (H x W): 12.9" x 9.9" (32.8 cm x 25.2 cm) • Nominal impedance: 8 ohms • Recommended amplifier power range: 10- 125 watts • Sensitivity (2.83V/1m): 89 dB • Frequency Range -3 dB from 45Hz-22kHz; -10dB from 35-30kHz | W383 UPC: 848592000486 | 415 € |
| W583 | <p>8" Micro-Ceramic Composite (MCC) Cone, Cast- Aluminum Frame Woofer</p> <ul style="list-style-type: none"> • 1" aluminum dome swiveling tweeter with waveguide • 3-position HF level control • Mounting depth: 3.8" (9.6 cm) • Weight: 6.4 lb (2.9 kg) / Shipping weight: 7.7 lb (3.5 kg) • Cutout dimensions (H x W): 11.9" x 8.9" (30.3 cm x 22.7 cm) • Includes zero-bezel magnetic grille • Grille finished dimension (H x W): 12.9" x 9.9" (32.8 cm x 25.2 cm) • Nominal impedance: 8 ohms • Recommended amplifier power range: 10- 135 watts • Sensitivity (2.83V/1m): 89 dB • Frequency Range -3 dB from 40Hz-25kHz; -10dB from 30-30kHz | W583 UPC: 848592000493 | 530 € |
| W783 | <p>8" Micro-Ceramic Composite (MCC) Cone, Cast- Aluminum Frame High-Output Woofer</p> <ul style="list-style-type: none"> • 1" aluminum dome swiveling high-output tweeter with waveguide • 3-position HF level control • LF boundary compensation • Mounting depth: 3.7" (9.4 cm) • Weight: 7.1 lb (3.2 kg) / Shipping weight: 8.6 lb (3.9 kg) • Cutout dimensions (H x W): 11.9" x 8.9" (30.3 cm x 22.7 cm) • Includes zero-bezel magnetic grille • Grille finished dimension (H x W): 12.9" x 9.9" (32.8 cm x 25.2 cm) • Nominal impedance: 8 ohms • Recommended amplifier power range: 10- 150 watts • Sensitivity (2.83V/1m): 89 dB • Frequency Range -3 dB from 36Hz-28kHz; -10dB from 25-35kHz | W783 UPC: 848592000509 | 705 € |

IN-CEILING & IN-WALL ARCHITECTURAL LOUDSPEAKERS



9" In-Wall Loudspeakers



| Model Name | Description | Material Number | MSRP |
|--------------------|--|-----------------------------------|-----------------------|
| W893 | <p>9" Micro-Ceramic Composite (MCC) Cone, Cast-Aluminum Frame High-Output Woofer</p> <ul style="list-style-type: none"> • 3.5" micro-ceramic composite (MCC) cone, cast-aluminum frame high-output midrange • 1" aluminum dome swiveling high-output tweeter with waveguide • 3-position HF level control • LF boundary compensation • Advanced high-order crossover network • Mounting depth: 3.7" (9.4 cm) • Weight: 10.8 lb (4.9 kg) / Shipping weight: 12.8 lb (5.8 kg) • Cutout dimensions (H x W): 17.4" x 11.6" (44.3 cm x 29.5 cm) • Includes zero-bezel magnetic grille • Grille finished dimension (H x W): 18.5" x 12.7" (47.0 cm x 32.3 cm) • C-2 fastening mechanism • Compatible with wall material thickness range: 0.5" – 2.0" (1.3 cm – 5.0 cm) • Nominal impedance: 8 ohms • Recommended amplifier power range: 10- 200 watts • Sensitivity (2.83V/1m): 89 dB • Frequency Range -3 dB from 32Hz-28kHz; -10dB from 23-35kHz | <p>W893 UPC: 848592000523</p> | <p>1.175 €</p> |
| Fire Rated Backbox | Fire (1 hour) and Plenum Rated Steel Backbox for W893 In-wall Loudspeaker | FBB9 | 100 € |

| | |
|-------------------------------|--|
| Note on Fire Rated Back Boxes | <p>Check local fire and building codes for the type of wall construction and thickness required to meet appropriate fire ratings.</p> <p>Standards and Ratings Tested (Subject to Change)</p> <p>a) ASTM E 119-00 REV A 2000-07-10 and E119-05 Standard Test Methods for Fire Tests of Building Construction and Materials</p> <p>b) NFPA 251 1999-00-00 Standard Methods of Tests of Fire Endurance of Building Construction and Materials(National Fire Codes, vol. 6)</p> <p>c) UL 263 1997-02-27 UL Standard for Safety Fire Tests of Building Construction and Materials Twelfth Edition; Reprint with Revisions Through and including 06/02/1998</p> <p>d) ULC CAN/ULC-S101 -M89 1989-00-00 and UBC 7-1 Standard Methods of Fire Endurance Tests of Building Construction and Materials</p> <p>e) UL 2043 1996-12-02 UL Standard for Safety Fire Test for Heat and Visible Smoke Release for Discrete Products and Their Accessories Installed in Air-Handling Spaces Second Edition; Reprint with Revisions Through and Including June 27, 2001</p> |
|-------------------------------|--|

ARCHITECTURAL LOUDSPEAKERS

In-Wall Subwoofer System



| Model Name | Description | Material Number | MSRP |
|------------|---|-----------------|---------|
| B28W | <p>In-wall Subwoofer</p> <ul style="list-style-type: none"> • Dual 8" (200mm) low-profile, long-throw, Klippel-optimized, metal cone woofers • Front-firing drivers with sealed back box for superior acoustic tuning • Gold-plated speaker terminals • Zero-bezel, magnetically-attached grille • Mounting cutout size (H x W): 23-1/2" x 14-1/2" (596.9mm x 368mm) • Sensitivity (2.83V/1m): Variable using the SA1000 • Nominal impedance: 8 ohms • Required Amplifier: Revel SA1000, in EQ Switch Position Type 2 • SPL (CEA2010DB): 107dB • Dimensions (H x W x D): 25-3/8" x 16-1/2" x 4" (645mm x 419mm x 102mm) • Weight: 28.4 lb (12.9kg) per speaker | REVB28W | 1.175 € |
| SA1000 | <p>Amplifier</p> <ul style="list-style-type: none"> • User-adjustable Single-band PEQ - Room Equalization • Short-circuit and over-current protection • Over-temperature compensation • Two dual banana output connectors for easy connection • Rated output power (RMS) into the minimum impedance of 4 Ohms: 700 Watts (350W per subwoofer) • Peak power: 1500 Watts (750W per subwoofer) • Rated Impedance: 4 Ohms • Input sensitivity to 1W @ 50Hz: 16.3mVrms +/- 1dB (Single input driver) Gain = 41.7dB • Minimum AC Main power requirements: 100-120VAC-50-60Hz Model 700W 5A • Dimensions: H x W x D: 3.5" x 17" x 1.04" (88.9mm x 431.8mm x 280.3mm) • Weight: 14 lb (6.35kg) | REVSA1000EP | 1.410 € |

ARCHITECTURAL LOUDSPEAKERS

Extreme Climate Loudspeakers



| Model Name | Description | Material Number | MSRP |
|------------|---|-----------------|-------|
| C363XC | <p>6 1/2" Flush-Mount Aluminum Cone, Cast-polymer Frame Woofer Extreme Climate Loudspeakers</p> <ul style="list-style-type: none"> • 1" Black Aluminum Dome Tweeter with Waveguide • Mounting Depth: 2.72" (69.1mm) Deep • Weight: 3.1 lb (1.41 kg) / Shipping Weight: 4.6 lb (2.1 kg) • Includes an extreme climate round zero-bezel magnetic grille • Round Grille Finished Dimension (Dia.): 9.1" (23.1 cm) • Cutout Dimensions (Dia.): 8" (20.3 cm) • Nominal impedance: 8 ohms • Recommended amplifier power range: 10- 100 watts • Sensitivity (2.83V/1m): 85 dB • Frequency Range -3 dB from 50-15 kHz; -10dB from 36-18 kHz | C363XC | 295 € |
| C383XC | <p>8" Flush-Mount Aluminum Cone, Cast-polymer Frame Woofer Extreme Climate Loudspeakers</p> <ul style="list-style-type: none"> • 1" Black Aluminum Dome Tweeter with Waveguide • Mounting depth: 2.69" (68.3mm) Deep • Weight: 3.9 lb (1.8 kg) / Shipping Weight: 5.9 lb (2.7 kg) • Includes an extreme climate round zero-bezel magnetic grille • Round grille finished dimension (dia.): 10.7" (27.2 cm) • Cutout dimensions (dia.): 9.6" (24.4 cm) • Nominal impedance: 8 ohms • Recommended amplifier power range: 10- 100 watts • Sensitivity (2.83V/1m): 87 dB • Frequency Range -3 dB from 45-15 kHz; -10dB from 33-18 kHz | C383XC | 355 € |

LANDSCAPE SPEAKERS

Extreme Climate Loudspeakers (cont.)



| Model Name | Description | Material Number | MSRP |
|------------|--|-----------------|---------|
| L41XC | 2-way 4" Landscape Satellite <ul style="list-style-type: none"> • 4" Micro Ceramic Composite Aluminum Cone Woofer • 0.75" Micro Ceramic Composite Aluminum Dome Tweeter • Recommended amplifier power: 60W Max • 70V transformer taps: 7.5W, 15W, 30W, 60W • Voltage: 70V • Rated impedance: 4 Ohm in bypass mode • Sensitivity: 83dB (2.83V @ 1M) in bypass mode • Frequency response: 100Hz-20kHz @ -3dB • Crossover frequency: 5.5kHz • Dimensions (L x W x H): 9.2" (23.2cm) x 6.5" (16.4cm) x 11.3" (28.5cm) • Weight: 9.9 lb (4.5kg) | REVL41XC | 800 € |
| L42XC | 2-way Dual 4" Landscape Bollard <ul style="list-style-type: none"> • Two 4" Micro Ceramic Composite Aluminum Cone Woofer • 1" Micro Ceramic Composite Aluminum Dome Tweeter • Recommended amplifier power: 60W Max • 70V transformer taps: 7.5W, 15W, 30W, 60W • Voltage: 70V • Rated impedance: 4 Ohm in bypass mode • Sensitivity: 86dB (2.83V @ 1M) in bypass mode • Frequency response: 80Hz-20kHz @ -3dB • Crossover frequency: 2.9kHz • Dimensions (L x W x H): 8.58" (21.8cm) x 8.58" (21.8 cm) x 33.7" (85.5cm) • Weight: 20.7 lb (9.4kg) | REVL42XC | 1.340 € |
| L42MXC | Optional mounting bracket for L42XC | REVL42MXC | 110 € |
| L12XC | 12" Landscape Burial Subwoofer <ul style="list-style-type: none"> • 12" Anodized Aluminum Cone Subwoofer • Recommended amplifier power: 250W Max • 70V transformertaps: 31.75W, 62.5W, 125W, 250W • Voltage: 70V • Rated impedance: 8 Ohm without transformer • Sensitivity: 86dB (2.83V @ 1M) without transformer • Frequency response: 25Hz-100Hz @ -3dB • Dimensions (L x W x H): 35" (88.7cm) x 18" (45.5cm) x 34.6" (87.8cm) • Weight: 66.4 lb (30.1kg) Speaker and port assembly; 8.2 lb (3.7kg) rock transformer | REVL12XC | 3.210 € |

Terms and Conditions of Sale

THIS PRICE LIST CANCELS ALL PREVIOUS LISTS AND IS VALID UNTIL FURTHER NOTICE.

ALL PRICES, SPECIFICATIONS, APPEARANCE, and TERMS AND CONDITIONS OF SALE ARE SUBJECT TO CHANGE WITHOUT NOTICE.

E&OE

PRICES EFFECTIVE October 2021



HARMAN Luxury Audio Group
The West Wing, Stirling House,
Waterbeach, Cambridge.
CB25 9PB
Phone: +44 (0)1223 203200
Orders: luxurysales@harman.com
Technical Support: csupport@harman.com

www.revelspeakers.com

© 2021 HARMAN International Industries, Incorporated. All rights reserved.

Revel and the Revel logo are trademarks of HARMAN International Industries, Incorporated, registered in the United States and/ or other countries. HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC. SACD is a trademark of Sony Corporation. VXP is a registered trademark of Sigma Designs, Inc., in the United States and/or other countries. All rights reserved.